11 Publication number:

0 **281 946** A2

(2)

EUROPEAN PATENT APPLICATION

2 Application number: 88103279.1

1 Int. Cl.4 G01V 1/40, G10K 11/16


2 Date of filing: 03.03.88

Priority: 09.03.87 US 2320814.04.87 US 38327

- ② Date of publication of application: 14.09.88 Bulletin 88/37
- Designated Contracting States:
 DE FR GB NL

- Applicant: Bolt Technology Corporation
 Four Duke Place
 Norwalk Connecticut 06864(US)
- Inventor: Cheiminski, Stephen V.
 63 Sidecut Road
 West Redding Connecticut 06896(US)
- Representative: Vossius & Partner Siebertstrasse 4 P.O. Box 86 07 67 D-8000 München 86(DE)
- Tube wave attentuation method, system and apparatus for use in liquid-containing wells.
- An inflatable attenuator having an inflatable resilient bladder enclosed by a perforated protective cylindrical housing is positioned in a liquid column in a well below (and if desired another inflatable attenuator is also positioned above) an impulsive energy source in the liquid column. The housing has an exterior diameter slightly less than the interior diameter of the well. The bladder is inflated when in the liquid column by gas supplied from a pressurized gas container attached to the attenuator or is supplied with pressurized gas through a hose line from a source of pressurized gas located on the surface of the Earth near the mouth of the well. A pressure-regulator responsive to the ambient hydrostatic pressure in the liquid column near the pressure regulator serves to maintain the pressure of the gas within the bladder at a regulated pressure at least equal to the ambient pressure in the liquid column where it is located. A pressure-relief valve releases pressurized gas from the bladder to prevent the pressure inside of the bladder from exceeding a predetermined differential in pressure between the inside of the bladder and ambient hydrostatic pressure so that the bladder will not rupture when the attenuator is being elevated in the well. The inflated bladder attenuates tube waves traveling along th Liquid column in the well from an impulsive source of seismic energy waves when employed in the liquid column above or below the energy source. The upwardly traveling tube waves may alternatively be

dissipated by releasing numerous gas bubbles in the upper portion of the liquid column to generate a bubble barrier in the upper portion of the liquid column. A further embodiment includes two bladders, including a tapered upper bladder which flares outwardly and downwardly and a cylindrical lower bladder. The perforated protective housing is omitted, and enlarged annular shoulders protect these bladders from abrasion against the wall of the well.



1 Publication number:

0 281 946 A3

12

EUROPEAN PATENT APPLICATION

- (2) Application number: 88103279.1
- 2 Date of filing: 03.03.88

(9) Int. Cl.4: G01V 1/40 , G10K 11/16 , G01V 1/04

- Priority: 09.03.87 US 23208 14.04.87 US 38327
- Date of publication of application: 14.09.88 Bulletin 88/37
- Designated Contracting States:
 DE FR GB NL
- Date of deferred publication of the search report: 30.08.89 Bulletin 89/35
- Applicant: Bolt Technology Corporation
 Four Duke Place
 Norwalk Connecticut 06854(US)
- inventor: Chelminski, Stephen V.
 63 Sidecut Road
 West Redding Connecticut 06896(US)
- Representative: Vossius & Partner Siebertstrasse 4 P.O. Box 86 07 67 D-8000 München 86(DE)
- Tube wave attentuation method, system and apparatus for use in liquid-containing wells.

 An inflatable attenuator (40) having an inflatable resilient bladder (46) enclosed by a perforated protective cylindrical housing is positioned in a liquid column in a well (10) below (and if desired another inflatable attenuator is also positioned above) an impulsive energy source (20) in the liquid column. The housing (42) has an exterior diameter slightly less than the interior diameter of the well (10). The bladder (46) is inflated when in the liquid column by gas supplied from a pressurized gas container attached to the attenuator or is supplied with pressurized gas through a hose line from a source of pressurized gas located on the surface of the Earth near the mouth of the well. A pressure-regulator responsive to the ambient hydrostatic pressure in the liquid column near the pressure regulator serves to maintain the pressure of the gas within the bladonder at a regulated pressure at least equal to the ambient pressure in the liquid column where it is located. A pressure-relief valve (50) releases pres-Surized gas from the bladder to prevent the pressure inside of the bladder from exceeding a predetermined differential in pressure betw en the inside of the bladder and ambient hydrostatic pressure so that the bladder (46) will not rupture when the attenuator (40) is being elevated in the well. The inflated blad-

der (48) attenuates tube waves (32) traveling along the liquid column in the well (10) from an impulsive source (20) of seismic energy waves when employed in the liquid column above or below the energy source. The upwardly traveling tube waves (35) may alternatively be dissipated by releasing numerous gas bubbles (72) in the upper portion of the liquid column to generate a bubble barrier in the upper portion of the liquid column. A further embodiment includes two bladders, including a tapered upper bladder which flares outwardly and downwardly and a cylindrical lower bladder. The perforated protective housing is omitted, and enlarged annular shoulders protect these bladders from abrasion against the well of the well.

Tube-Wave Attenuation Method, System and Apparatus for use in Liquid-Containing Wells

10

BACKGROUND

The present invention relates to seismic exploration of the structure of the Earth Surrounding liquid-containing wells, and more particularly to the type of exploration wherein powerful acoustical impulses are produced by a sound source lowered into the liquid in a well for causing acoustical impulses to penetrate the wall of the well adjacent to the sound source and to travel through the surrounding structure to geophones for recording and analyzing the resulting electrical signals produced by the respective geophones in response to the acoustical impulses reaching them after propogation through the Earth's structure.

A problem which is encountered in such seismic exploration results from the fact that the liquidfilled well bore is a good conductor of tube waves with the inner surfaces of the well wall acting as a wave guide. Thus, relatively strong tube waves travel along the well bore downwardly and upwardly from the sound source each time that it is fired. When these tube waves traveling down along the well bore reach the bottom of the well, or a discontinuity in the liquid-filled well bore, they are strongly reflected, but a significant amount of the energy in these tube waves becomes converted into compressional body waves propagating out from the discontinuities in the well through the surrounding structure of the Earth. Similarly, when these tube waves traveling up along the liquid-filled bore reach the top surface of the liquid, they are strongly reflected, but a significant amount of their energy becomes converted into compressional body waves propagating out from the top of the liquid column through the surrounding structure of the Earth.

These compressional body waves, i.e., sound (accoustical) waves, propagated outwardly through the Earth's structure from the bottom and top of the liquid column and other discontinuities within the well bore, may be called "secondary sound (or acoustical) waves", and they also reach the geophones but at a later time than did the compressional body waves travelling directly from the impulse energy (sound) source. Shear waves travelling directly from the impulsive energy source are propagated more slowly than compressional body waves, about half as fast, and thus the secondary sound waves cause more interferenc with the shear waves than with the compressional body waves. This e secondary sound waves caus this records of signals from the geophones to be cluttered and confusing with unwanted signals which

are attempted to be removed during processing of the records before their final graphic display.

The tube waves which travel downwardly or upwardly from the sound source along the liquid-filled well bore are being guided along the side wall of the well bore, and the particle motions of these tube waves occur in both the well liquid and the adjacent solid material of the casing or rock and are in the nature of "Stoneley Waves".

SUMMARY

It is an object of this invention to provide a tube wave attenuation method, system and apparatus for use with a sound source lowered into the liquid in a wall for attenuating tube waves travelling from the sound source downwardly or upwardly along the liquid column.

In carrying out this invention in one illustrative embodiment thereof, a method is provided for attenuating unwanted tube waves in a liquid column in a well comprising the steps of lowering an inflatable attenuator into the liquid column in the well and supplying pressurized gas to the inflatable attenuator. The supply of pressurized gas to the attenuator is regulated to be at least equal the ambient pressure in the liquid column near the attenuator in the well. An impulsive energy source is lowered in the liquid column in the well above the inflatable attenuator to be fired for seismic exploration purposes. The tube waves travelling down along the liquid column are attenuated by the attenuator prior to reaching the bottom of the well in order to prevent or minimize secondary acoustical waves from emanating from discontinuities in the well and from the bottom of the well, which would otherwise be caused as a result of the tube waves travelling down the column of liquid in the well.

An attenuator may also be provided above the energy source for attenuating tube waves travelling upwardly from the source along the column to prevent secondary waves from being propagated out from discontinuities in the well and from the top of the liquid column. Upper attenuation may also be obtained by creating gas bubbles in the upper portion of the liquid column. Such bubbles may be provided from a separate source or from th source supplying pressurized gas to the inflatable attenuator. In addition, pr ssurized gas may be released from the inflatable attenuator into the liquid column to prevent the internal pr ssure of the inflatable attenuator from exceeding a predetermined differential relative to ambient liquid pres-

5

10

sure for preventing damage to the inflatable attenuator when it is raised from a lower to a higher elevation in the well.

Advantageously, the tube-wave attenuator apparatus, system and method of the present invention effectively dissipate tube waves emanating from an energy source fired in the well, which travel either upwardly or downwardly along a column of liquid in a well for preventing or minimizing the resulting interference or confusion with respect to the desired compressional and shear waves travelling directly into the Earth's structure from the sound source for reaching geophones located in other wells or elsewhere around the first well. The present apparatus system and method eliminate or minimize the resulting secondary signals for alleviating the confusion problems discussed above.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention together with further objects, aspects, features and advantages will be more clearly understood from the following description taken in connection with the accompanying drawings in which the same reference numerals are used to identify the same elements throughout the various views.

FIGURE 1 is a diagrammatic illustration of the prior art problems showing the undesired effects of tubes waves caused by a sound source lowered and fired in a well containing a liquid column with geophones located nearby, and showing the paths of the resultant secondary waves emanating from the bottom of the well and also from the top of the liquid column in the well.

FIGURE 2 illustrates an inflatable attenuator embodying the present invention in certain aspects of the invention.

FIGURE 3 illustrates one embodiment of the method and system of the present invention utilizing the inflatable attenuator of FIG. 2 in a well containing a liquid column with the attenuator positioned below an impulsive energy source used for seismic exploration.

FIGURE 4 shows an embodiment similar to FIG. 3 using a common gas supply near the mouth of the well for supplying both the impulsive energy source as well as the inflatable attenuator.

FIGURE 5 illustrates another embodiment of the method and system of the present invention using two inflatable attenuators, one above and one below the impulsive en rgy source in the welf.

FIGURE 6 illustrates another embodiment similar to FIG. 5 in which both inflatable attenuators as well as the impulsive source are fed from a single pressurized gas supply line.

FIG. 7A shows the upper portions of another embodiment of an inflatable attenuator embodying the present invention in certain aspects of the invention.

FIG. 78 shows the lower portions of the inflatable attenuator of FIG. 7A.

DESCRIPTION OF THE PREFERRED EMBODI-

Referring now to FIG. 1, which in effect is used to describe the prior art problem, a well 10 which has been drilled in the Earth 12 contains a column of liquid 14 having a top surface 16 and a bottom surface 18 at the lower end of the well. This well has a mouth 17 and it may or may not include a casing or liner of steel 19. The invention is applicable in either case. An impulsive energy source 20 for example, a marine seismic airgun such as shown in my U.S.Patents Nos. 3,997,021 and 4,472,794 and/or a hydro gun such as shown in my U.S. Patent No. 4,234,052 is suspended from a cable or line 22. This sound energy source is illustrated as being fired which generates selsmic waves 24, including compressional body waves and shear waves, which emanate in all directions from the energy source 20 and penetrate the wall of the well 10 to travel through the surrounding Earth structure 25 as illustrated by the path arrow 26 leading to geophones 28 on the surface of the Earth 12 for recording and analyzing the resulting electrical signals produced by the geophones in response to the acoustical impulses 28 reaching them after propagation through the Earth's structure 25.

It is to be noted that the geophones 28 may be positioned on the Earth's surface surrounding the well mouth and/or may be positioned below the surface of the Earth, for example, in other holes or wells; or they may be positioned on the Earth at a different or considerably lower elevation, for example, on the flank of a nearby valley. The geophones 28 may also be positioned in other liquid-containing wells which are located reasonably near to the well 10, in which event the geophones 28 are adapted to be submerged and then may be structured as hydrophones. The waves 24 propagated directly from the source 20 via a path indicated by the arrow 26 are the desired primary waves 27 reaching the geophones or hydrophones 28. It will be understood that these primary waves 27 may have been reflected and/or refracted by the various geological formations 29, 30 and 31 in the vicinity of the well 10 before these desired primary waves reach the geophones or hydrophones 28. Thus, the path 26 (or multiple paths) travelled by these primary waves in reaching each phon 28 is usually

25

not straight. The waves 27 are considered to be "primary waves", because they originated directly from the energy source 20, and they include compressional body waves and the slower-travelling shear waves. The arrow 26 is shown straight for convenience and clarity of explanation.

Since the liquid column 14 acts with the well wall as a good conductor of tube waves and the well bore acts as a wave guide, strong tube waves illustrated by the arrow 32 are propogated toward the bottom of the well 10 and reflect off from the bottom 18 generating what are referred to as secondary sound waves 33 emanating from the well bottom 18 as illustrated by the arrow 34. Strong tube waves also travel upwardly from the source 20 along the liquid column as illustrated by the arrow 35 to the top of the liquid column 14 and are reflected back downwardly, but during this reflection a substantial amount of compressional body waves (sound or acoustical waves) emanate from the top surface 16 and travel outwardly and downwardly as secondary waves 38 as illustrated by the arrow path 38. Such secondary waves are reflected or refracted by one or more formations 29 in the Earth 12 and reach the phones 28. These secondary waves 33 and 36 represent significant amounts of acoustical energy which reach the phones in addition to and at different moments from the primary sound waves 27. Therefore, these secondary sound waves 33 and 36 cause the signals recorded by the phones to become cluttered and confused with unwanted signals which must be removed during processing of the records before the final graphic display relating to the Earth's structure 25 can be made. This removal or compensation for unwanted signals is a difficult and time-consuming process and is not easy to accomplish and may only be accomplished partially. Accordingly, the present invention is directed to attenuating the tube waves 32 and 35 in the liquid column 14 before they reach the bottom 18 or top 16 of the liquid column, and preferably to attenuating the tube waves relatively near to the energy source 20.

FIG. 2 shows an inflatable attenuator, referred to generally with the reference numeral 40 which comprises a circular cylindrical steet housing or casing 42 which has an external diameter slightly 1 ss than the inside diameter of the well 10 and is perforated over its entire length with apertures or openings 44. The perforated cylindrical housing 42 encircles an inflatable bladder 48 of suitable material, such as rubber or a polymeric xpandable material, for example, an lastomeric material, e.g. neoprene rubber, nitrile rubber, silicone rubber, polyurethan, reinforced with strong fibers, for example, fibers of polyester or Kevlar, and having bladder-end terminating fittings 45 at each

reduced-diameter end. The resilient wall of the bladder 46 flares or tapers downwardly and outwardly as indicated at 43 immediately below the reduced-diameter upper end fitting 45. Similarly, at the lower end of the bladder 46 there is an upward and outward flare or taper of the bladder wall immediately above the lower end reduced-diameter fitting 45, as indicated at 43'. The bladder 48 is connected by a conduit 47 to a pressure-reducing and regulating valve 48 which is responsive to ambient pressure for maintaining the pressure within the inflatable bladder 46 slightly above the ambient pressure of the liquid in the well at the level to which the inflatable attenuator 40 is lowered. This pressure-reducing valve 48 is connected by a conduit 49 to a pressurized gas supply container 52. Thus, the bladder 46 is held in position within the housing 42 by its attachment via conduit 47 to the container 52. The inflatable bladder 46 carries a relief valve 50 which is responsive to the differential in pressure between the ambient liquid in the well and the pressure inside of the inflatable bladder 46.

The purpose of the valves 48 and 50 is to enable the supplying of pressurized gas into the interior of the bladder 46 as the inflatable attenuator 40 is being lowered in a well to keep the internal pressure in the bladder 46 at a pressure level somewhat above the ambient liquid pressure, for example, in the range from about 1 pound per square inch (p.s.i.) to about 8 p.s.i. above the ambient and thus to keep the bladder inflated on its way down while bleeding off pressure through the relief valve 50 when the inflatable attenuator 40 is being elevated in the well, so that the bladder will not rupture or burst from too much differential of inside-to-outside pressure on the way up in the well. For example, the relief valve 50 may be set to bleed open whenever the inside bladder pressure is 12 p.s.i. or more above ambient pressure. If the pressure-reducing and regulating valve 48 is selfventing, the relief valve 50 may be omitted.

The container 52 preferably of steel, containing compressed gas, usually air, is attached to the housing 42 by eyelets 54, cables or chains 56 and eyes 58 on a ring clamp 60 mounted on the container 52. Compressed gas from the container 52 is supplied through the pressure-reducing valve 48 to the bladder 48. The housing 42 is suspended from a hoisting ring 62 which is adapted to be attached to a lowering hoist cable 63 (FIG. 3). The ring 62 is attached by cables or chains 64 to eyelets 66 mounted in the top of the casing 42. When an inflatable attenuator 40 has a pressurized gas supply container 52 attached thereto as shown in FIG. 2, the inflatable attenuator may b considered a self-supplied or locally supplied unit. The attenuator 40 may also be supplied from a remotely located source 75 of pressurized gas, as explained later.

FIG. 3 illustrates one application of the inflatable attenuator 40 in the method and system of the present invention. A seismic exploration van or truck 70 carrying a high-pressure compressor 75 lowers via cable 63 the impulsive energy source 20 which has suspended from the lower end thereof on a cable 68 the inflatable attenuator 40 which is positioned below the energy source 20 in the well 10. High pressure gas, usually air, is fed from the pressurized gas source 75 via a high pressure hose line 80 to the energy source 20. When the impulsive energy source 20 is a hydro gun as disclosed and claimed in U.S. Patent No. 4,234,052, then there is a positive displacement high pressure water pump carried by the van 70 for charging the impulsive energy source. When the impulsive energy source is fired generating the seismic impulses 24, the primary sound waves 27 are propagated through the structure 25 of the Earth 12, as shown by the arrow 28, and reach the geophones or hydrophones 28 which receive these desired primary waves. The tube waves 32 travelling downwardly in the column of liquid 14 in the well 10 encounter the inflatable attenuator 40 which provides very poor sound coupling between the liquid 14 and the air-filled bladder 48. When the tube waves 32 encounter the tapered upper end 43 of the inflated bladder 48, they are absorbed and damped by the elongated bladder for there is a relatively long path in the axial direction relative to the attenuator 40. Little tube wave energy will succood in cetting past the attenuator 40 because of the surrounding well wall and the narrow annular clearance 71 between the well wall and the perforated housing 42. It is to be understood that the inflated bladder 48 (FiG. 2) essentially completely fills the perforated housing 46, and the wall of the bladder 46 is pressing radially outwardly being preferably spaced about 1/8th to about 1/2 of an inch from the inside surface of the perforated cylindrical housing 42. The openings or perforations 44 in the housing communicate with the inflatable bladder 48 which dissipates and attenuates or damps tube waves 32 in the narrow region 71 around the attenuator 40 and in the narrow annular region 77 (FIG. 2) between the bladder 48 and housing 42. The openings 44 have a size of about 3/16ths to about 5/16ths of an inch and comprise at least about 40% to about 60% of the total area of the housing 42.

In the mbodiment shown in FIG. 3, the tube waves 35 travelling to the top 16 of the liquid column 14 are attenuated using numerous bubbles 72 of air created by a low-pressure compressed air generator 73 feeding through a hose line 74 to an elongated porous probe 76 which discharges mul-

titudes of compressed air bubbles 72 into the upper portion of the liquid column 14 creating a substantial column 78 of bubbles of various sizes and random spacing which dissipate the tube waves 35. Accordingly, tube waves 35 travelling upwardly in the liquid column are attenuated by bubbles 72 while tube waves 32 travelling downardly in the liquid column 14 are attenuated by the inflatable attenuator 40 allowing the phones 28 to receive only or mainly those desired primary waves 27 which are transmitted directly from the seismic energy source 20.

In the method and system of FIG. 3 the tube wave attenuator 40 is supplied with pressurized gas from the closely associated gas supply container 52. In the method and system of FIG.4 now to be described, the tube wave attenuator 40 is supplied with pressurized gas from a source 75 on the Earth's surface 12.

The embodiment in FIG. 4 is similar to FIG. 3 except that high-pressure compressed gas, usually air; is supplied from the surface by a high-pressure hose line 80 extending to the energy source 20 and to the inflatable attenuator 40, thereby dispensing with the need for attaching the supply container 52 of compressed gas to the inflatable attenuator 40. Accordingly, a common source 75 of compressed air in the van is supplying both the impulsive energy source 20 and the inflatable attenuator 40 via hose line 80. In addition, if desired, this same source 75 may be used to supply the probe 76 to create a mass of air bubbles 78 near the top 16 of the column for attenuating upwardly traveling tube waves in that bubble mass 78. Alternatively, the separate single-stage low-pressure compressor 73 can be used to feed the probe 76. The compressor 75 is a high-pressure compressor, for example at least a triple-stage com pressor having an output pressure of at least 2,200 psi. The hose line 80 is connected through the pressure-reducing valve 48 to feed the interior of the bladder 48. The operation of the system in FIG. 4 and the method employed are the same as that shown in FIG. 3.

FIG. 5 shows another embodiment of the method and system employing the use of an inflatable attenuator 40 both below as well as above the impulsive energy source 20. These two inflatable attenuators 40 are utilized to attenuate tube waves traveling down the liquid column 14 in the well 10 and to attenuate tube waves traveling upwardly in the liquid column from the energy source 20. In the embodiment of FIG. 5 the compressed gas source 75 is shown mounted in the seismic exploration van 70. Compressed gas is fed through the line 80 to the seismic energy source 20. It is to be noted in FIG. 5 that each of the tube wave attenuators 40 has an associated nearby container 52 of compressed gas, usually air, for inflating the bladder

10

20

through a pressure-regulating valve 48.

FIG. 6 illustrates an alternative embodiment to FIG. 5 which utilizes a common pressurized gas supply 75 which feeds through a high pressure hose line 80 to the pressure-regulating valve 48 for inflatable bladder 46 of the upper attenuator 40. This hose line 80 also feeds to the energy source 20 and through a continuation of line 80 to the pressure-regulating valve 48 for the inflatable bladder 46 of the lower attenuator 40. The operation of the system and method of FIG. 6 are similar to those of FIG. 5 in that the upper attenuator 40 is used to attenuate upwardly traveling tube waves in the liquid column 14 while the lower attenuator 40 is used to attenuate tube waves traveling downwardly in this liquid column 14.

An advantage of using a single gas supply line 80 for feeding the energy source 20 and the attenuators 40 as shown in FIG. 6 resides in the ability to carry on very numerous firings of the seismic source 20 at various elevations without withdrawing the equipment from the well, which would become necessary if the pressurized gas in one of the containers 52 (FIG.5) were to become dissipated during the seismic surveying operations and thus need to be replenished.

Accordingly, method and system apparatus have been provided which effectively attenuate tube waves which are traveling up and down in a column of liquid in a well which would otherwise interfere with or confuse the seismic survey. By attenuating or eliminating these troublesome tube waves which add no useful information, more accurate and more informative seismic surveys are enabled to be made.

The "pressurized gas" for charging the impulsive energy source 20 and for generating the bubbles 72 is usually compressed air. In situations where it is desired to avoid usage of compressed air, for example because of the hazard of combustible gases or liquids in the well 10 or for other reasons to avoid an oxidizing gas, then the pressurized gas may be compressed nitrogen or carbon dloxide. Also, steam may be used to charge the energy source 20, and then a low-pressure compressor 73 is used to generate the gas bubbles 72.

Inviting attention back to FIG. 2, it is to be noted that the container 52 of pressurized gas can advantageously be mounted Inside of the bladder 46 by employing a container 52 which has a slim shape for providing an annular clearance space between the exterior of the pressure vessel 52 and the inside surface of th resilient, flexible wall of the bladder. Thus, the bladder remains resilient even though it houses the pressure vessel 52. By virtue of placing th pressure vessel 52 inside of the bladder 46, I ss compressed air is needed for

inflating a bladder of given size, and the overall length of the inflatable attenuator 40 and its supply source 52 is reduced. The compressed air or other gas in the pressure vessel 52 will last longer, because there is considerably less free space in the bladder to be inflated.

In order to mount the pressure vessel 52 within the bladder 46, the cables or chains 56 are attached to pad eyes (not shown) attached to the lower end fitting 45. Then, the conduit 49 from the pressure vessel 52 extends down through the lower end fitting 45 and extends down to the pressure regulating valve 48, which is located below the lower end fitting 45. The exposed portion of the conduit 49 includes an accessible Tee coupling with a shut off valve (not shown) for enabling the pressure vessel to be conveniently refilled with pressurized gas whenever needed without removing the pressure vessel from inside of the bladder.

FIGS. 7A and 7B show an inflatable attenuator 40A having a cylindrical inflatable lower bladder 46-2 and an upper inflatable bladder 46-1. The cylindrical lower bladder 46-2 is made of the same material as the generally cylindrical bladder 46 in FIG. 2. At the present time, tough, durable, resilient non-reinforced polyurethane is the preferred material for the tapered upper bladder 46-1, because it is desirable to position the attenuator 40 or 40A relatively close to the energy source for attenuating the tube waves as reasonably close to the energy source as practicable. Therefore, the upper bladder 46-1 becomes subjected to a powerful, impulsive change in pressure each time that the energy source is fired. Tough, durable, resilient polyurethane proves to be able to withstand successfully the resultant sudden large stresses involved. The upper bladder 46-1 tapers or flares outwardly and downwardly, for example, it has a relatively elongated generally conical configuration.

The support and axial trunk of this attenuator 40A comprises a strong rigid tube 90, for example, of steel, having a pipe-threaded socket 92 at its upper end. Thus, the attenuator 40A can be suspended in a well 10 by attaching a hose line 74 or 80 to the socket 92 by providing a threaded coupling on the lower end of the hose line 74 or 80 which screws into the socket 92. As shown in FIGS. 4 and 6, this attenuator 40A can be suspended below an energy source 20 in a well by extending a section of high pressure hose line 80 down from the energy source 20 and attaching it to the socket 92.

In order firmly to secure the upper end of the tapered bladder 48-1 in place, the exterior surface of the axial tube frame 90 is threaded at 94 immediately below the socket 92, and a pair of clamprings 96 encircle the upper end portion of the bladder 46-1 overlying this threaded region 94.

in order firmly to secur the lower end of the tapered conical bladder 46-1 and the upper end of the circular cylindrical bladder 46-2, there is a mounting seat member 98 for example, of steel, rigidly attached to the axial tube 90, for example. by welds at 100. The exterior surface of the seat member 98 is threaded in an upper region 94 for receiving the lower end portion of the tapered bladder 48-1 secured by a pair of clamping rings 98 and is also threaded in a lower region 94 for receiving the upper end portion of the cylindrical bladder 46-2 secured by another pair of clamp rings 96. For preventing abrasion of the bladders 48-1 or 46-2 against the well wall, a large O-ring 102 of resilient polymeric material, for example, polyurethane is mounted in a retainer groove 104 between the two bladders 48-1 and 48-2 for serving as a bumper or protective annular shoulder.

During assembly, the lower bladder 48-2 is slid down over the seat member 98, and the O-ring bumper 102 is installed after the lower bladder 46-2 has been installed. Then, the upper bladder 48-1 is installed after the O-ring bumper 102 is in place.

As seen in FIG. 7B, the axial tube frame 90 extends down a considerable distance below the mounting seat member 98 and is securely attached, for example, by welding 100, to a lower end fixture 106. The lower end of the cylindrical bladder 48-1 is firmly secured to an externally threaded region 94 of the fixture 108 by a pair of clamp rings 98. The bore 108 of the tube frame 90 communicates through a passageway 110 in the fixture 108 with a pressure-reducing and regulating valve 48. This regulating valve 48 is mounted in an axial socket 112 in the fixture 108, being retained by a removable retainer sleeve 114 which is held by a removable end fitting 116 fastened to the fixture 106 by machine screws 118. The pressurereducing valve 48 is sealed to the passageway 110 by an O-ring 120. The pressurized gas, usually compressed air, of regulated pressure is fed from the valve 48 through a passageway 122 in the fixture 106 communicating with the interior of the bladder 48-2, and an O-ring 124 seals the valve 48 to the passageway 122. As seen in FIG. 7A, the interior of the bladder 48-2 communicates with the interior of the bladder 46-1 through a passageway 126 in the mounting seat member 98. Thus, the valve 48 supplies both bladders with pressurized gas at the desired pressure compared with ambient, for example, about 1 to about 8 p.s.i. above ambient.

In order for the pressure-reducing and regulating valve 48 to sense ambient pressure, there is an axial passag 128 in the nd fitting 116. For protecting the valve 48 from dirt and grit, a partici filter 130 is held in the passage 128 by a snap ring 132; this filter 130 comprises a fibrous mat sand-

wiched between two discs each having numerous ap rtures.

If the adjustable pressure-reducing and regulating valv 48 is also a self-venting valve set to vent at a pressure above the regulated pressure, for example, set to vent at about 12 p.s.i., then a pressure-relief valve is not needed.

If a pressure-relief valve 50 is included, it is mounted in a transverse socket 134 communicating through a passage 136 with the passage 122 communicating with the interior of the bladders 46-1 and 46-2. The other end of the drilled passage 136 is plugged at 138. The pressure-relief valve 50 is held in its socket 134 by a threaded ring 140 and communicates with ambient liquid through a port 142 in this ring.

It is to be noted that the fixture 108 is enlarged in diameter below the region 94 where the bladder 48-2 is attached, and this enlargement serves as a protective annular shoulder below the lower end of the bladder for preventing abrasion of the bladder 48-2 against the well wall.

In operation, pressurized gas, usually compressed air, supplied into the socket 82 feeds down through the bore 108 of the tubular support 90 and feeds through passage 110 to the pressure-reducing and regulating valve 48. Pressurized gas at the desired pressure level relative to the pressure of ambient liquid is supplied by the valve 48 through the passageway 122 into the interiors of the two bladders. When the attenuator 40A is raised in the well to a region of reduced ambient pressure, the pressure relief valve 50 bleeds away pressurized gas from the passageways 122, 138 through the port 142 to ambient. If the valve 48 is self-venting, then pressurized gas bleeds away from the passageway 122 through the valve 48 through the exial passage 128 and through the filter 130 to ambient.

As used herein, the term "phones" is intended to include geophones and hydrophones.

Regardless of whether the description of the precise nature of tube waves in the introduction is incomplete or inaccurate in some respects, it is fully accurate that the attenuation method, system and apparatus of the present invention are very effective and advantageous in eliminating or dramatically reducing the problems caused by unwanted tube waves occurring in a well when using an impulsive seismic energy (sound) source in a liquid-containing well in the earth for seismic surveying of the structure of the Earth around the well.

In the event that the energy source 20 is a vibrator, and if a vibrator causes tube waves in the liquid-containing well, then the present invention may be used to advantage with such a vibrator energy source.

Claims

- 1. A method for attenuating unwanted tube waves (32, 35) generated in a liquid column (14) in a well (10) as a result of operating a seismic energy source (20) in the liquid column in the well comprising the steps of: lowering an inflatable attenuator (40, 42, 48 or 40A, 46-1, 46-2) down into the liquid column in the well, supplying pressurized gas to said inflatable attenuator, regulating (48) the pressurized gas supplied to said inflatable attenuator to at least be equal to the ambient pressure in said liquid column near said attenuator, lowering the seismic energy source (20) down into said liquid column in said well to an elevation in the well different from the elevation of said inflatable attenuator, and operating said seismic energy source, whereby tube waves traveiling along said liquid column from sald energy source to said inflatable attenuator are attenuated by encountering said attenuator prior to reaching an end (18 or 16) of the liquid column in said well.
- 2. The method as claimed in Claim 1 including the steps of: lowering said attenuator (40, 42, 46 or 40A, 46-1, 46-2) to a level in the well below said energy source, lowering a second inflatable attenuator (FIGS. 5 and 6) in said well to a level above said energy source prior to operation of said energy source for attenuating tube waves travelling in said liquid column downwardly and upwardly from said energy source before such tube waves reach the bottom (18) or the top (16) of said liquid column.
- 3. The method as claimed in Claim 1 or 2 including the steps of: raising said inflatable attenuator (40, 42, 46 or 40A, 46-1, 46-2) upwardly in the liquid column in the well, and releasing (48 or 50) pressurized gas from said inflatable attenuator into said liquid column to prevent the internal pressure of said inflatable attenuator (46 or 46-1, 46-2) from exceeding a predetermined differential above ambient pressure of the liquid near said attenuator for preventing damage to the inflatable attenuator upon being raised from a lower to a higher elevation in said well.
- 4. The method as claimed in Claim 2 including the step of: supplying pressurized gas to said first and second inflatable attenuators from a common source (75) of pressurized gas.
- 5. The method as claimed in Claim 1, 2, 3 or 4, wherein: said inflatable attenuator (40, 42, 48 or 40A, 46-1, 46-2) is elongated for providing a relatively long path in the axial direction relative to the diameter of the actuator and has an external diamter slightly less than the internal diamter of the well for attenuating tube waves in the narrow annular clearance (71) between the well wall (19) and the inflatable attenuator.

- 8. The method as claimed in Claim 5, wherein: said inflatable attenuator 40, 42, 46 or 40A, 46-1, 46-2) has an axial length at least about 5 times its external diameter and said narrow annular clearance (71) is less than about one-fifth of the external diameter of the inflatable attenuator.
- 7. The method as claimed in Claim 5 or 6, wherein: said inflatable attenuator (40, 42, 46 or 40A, 46-1, 48-2) has an inflatable bladder (46 or 46-1) with a tapered end 43, 43' or 48-1 facing toward said selsmic energy source (20).
- 8. A system for seismic surveying of the structure of the Earth (12) in which phones (28) are arranged near a well (10) in the Earth containing a fiquid column (14), a seismic energy source (20) is positioned submerged in said liquid column for operating said energy source for transmitting seismic energy waves (27) through the Earth to the phones for gathering data abour geologic formations in the Earth surrounding said well, said system comprising: an inflatable attenuator (40, 42, 46 or 40A, 46-1, 46-2), support means (63, 68) for positioning said inflatable attenuator in said liquid column at a different elevation in said liquid column from said seismic energy source (20) for attenuating tube waves (32, 35) travelling along said liquid column from said source to said inflatable attenuator, means for supplying pressurized gas (52 or 75) into said inflatable attenuator (46 or 46-1, 46-2) for inflating said attenuator in said well, and regulating means (48) for regulating the pressurized gas supplied to said inflatable attenuator to at least be equal to the ambient pressure in said liquid column near said attenuator, whereby tube waves (32,35) travelling along said liquid column are attenuated by encountering said attenuator before the tube waves reach an end (16,18) of said liquid column, thereby minimizing the transmission of secondary selsmic energy waves (33, 36) from discontinuities (16, 18) within the liquid column upon reflections of tube waves from said discontinuities.
- 9. The system as claimed in Claim 8, wherein: said inflatable attenuator includes an axially elongated inflatable resilient bladder (46 or 46-1, 48-2), and protective means (42 or 102, 108) having a larger external diameter than said axially elongated inflatable resilient bladder for preventing abrasion of the bladder against a wall surface (19) of a well (10).
- 10. The system as claimed in Claim 9, wherein: said protective means (42) extends longitudinally around said axially elongated inflatable resilient bladder (48) and includes a multitude of openings (44), and said protective means is spaced radially outwardly from said bladder.
- 11. The system as claimed in Claim 10, wherein: said axially elongated inflatable resilient bladder (46) has an axial length at least about 5

times its external diameter, and said protective means (42) is spaced radially outwardly from said axially elongated inflatable resilient bladder by a radial spacing in the rang from about 1/8 of an inch (about 3 mm) to about 1/2 of an inch (about 13 mm) for providing an elongated narrow annular region (77) between said bladder and said protective means.

12. The system as claimed in Claim 9, 10 or 11, including pressure-relief means (48 or 50) responsive to ambient liquid pressure and responsive to the pressure of the gas within said bladder for automatically releasing pressurized gas from said bladder (46 or 46-1, 46-2) when the differential in pressure between the ambient pressure in the liquid column (14) near said attenuator and the internal pressure in said bladder exceeds a predetermined amount for preventing damage to said bladder when the attenuator is being elevated in the liquid column in said well (10).


13. The system as claimed in Claim 9, 10, 11 or 12, wherein: said inflatable attenuator (40, 42, 46 or 40A, 48-1, 48-2) includes a container of pressurized gas (52) associated with said inflatable resilient bladder (48) and which is lowered into said well (10) along with said inflatable bladder for inflating said bladder with pressurized gas, and said regulating means (48) regulates the pressure of the pressurized gas inflating said bladder.


14. The system as claimed in Claim 9, 10, 11 or 12, wherein: said inflatable resilient bladder (48 or 46-1, 46-2) is supplied with pressurized gas from a source of pressurized gas (75) located near the mouth of the well, and said regulating means (48) regulates the pressure of the pressurized gas inflating said bladder.


15. The system as claimed in Claim 9, 10, 11, 12, 13 or 14, wherein: said protective means (42) is an axially elongated hollow cylindrical member of strong material having numerous apertures (44) therein encircling said axially elongated inflatable resilient bladder, and said hollow cylindrical member is spaced radially outwardly from said inflatable resilient bladder.


16. The system as claimed in Claim 8, 9, 10, 11, 12, 13, 14 or 15, wherein: said inflatable attenuator (40, 42, 46 or 40A, 46-1, 46-2) includes resilient means (43, 43' or 46-1) which tapers and progressively increases in diameter in a direction away from said seismic energy source (20).


17. The system as claimed in Claim 16, wherein: said resilient means (46-1) has a relatively elongated generally concical configuration having an axial length gr ater than the largest external diam ter of said resilient means.























.•

EP 0 281 946 A3





EUROPEAN SEARCH REPORT

Application Number

EP 88 10 3279

	DOCUMENTS CONS	SIDERED TO BE RELEVA	NT]
Category	Citation of document with of relevant	indication where accessive	Relevant to claim	CLASSIFICATION OF THE
X	PATENT ABSTRACTS O	F JAPAN, vol. 7, no. 2nd February 1983; & UYOU CHISHITSU	1,3,5,7,8,16	G 01 V 1/40 G 10 K 11/16 G 01 V 1/04
A			6,12,13	
A	US-A-3 054 471 (K * Claim 1; figures	NUDSEN) 1-6 *	1	
A	US-A-3 982 606 (B * Abstract; figure	ERRY et al.) s 1-6 *	1	

				TECHNICAL FIELDS SEARCHED (Int. C.14)
				G 01 V G 10 K
 -	The present search report has b	oce drawn up for all claims]	
THF	Place of search HAGUE	Date of completion of the search		Exuminer
CATEGORY F CITED DOCUMENTS		29-05-1989	ANDERSON A.TH.	
X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure		E: tarilly patent	T: theory or principle underlying the invention E: earlier patient decument, but published on, or after the filing date D: document cited in the application L: document cited for other reasons	
	written disclosure	********	A: member of the same patent family, corresponding document	